

CASE IH: FOR THOSE WHO DEMAND MORE

WWW.CASEIH.COM

	JX 60	JX 70	JX 80	JX 90	JX 95
ENGINE					
Capacity (cm ³) / No. of cylinders / aspiration	2931 / 3 / nat-asp	2931 / 3 / turbo	3908 / 4 / nat-asp	4500 / 4 / turbo intercooled	4500 / 4 / turbo intercooled
Rated engine power ECE R120 ¹ [kW/hp(CV)]	43.5 / 59	50.5 / 69	58.5 / 80	65 / 88	70 / 95
Rated engine speed (rpm)	2500	2500	2500	2500	2500
Max. torque (Nm @ rpm)	207 @ 1500	250 @ 1500	279 @ 1500	375 @ 1300	390 @ 1300
Fuel tank capacity (litres)	92	92	92	92	92
TRANSMISSION*					
Type	Synchromesh, 4 speeds, 3 ranges, 30 or 40kph				
Number of speeds standard (FxFR)	12x12	12x12	12x12	12x12	12x12
Number of speeds with creeper optional (FxFR)	20x12	20x12	20x12	20x12	20x12
DRIVE AND STEERING					
Four-wheel drive engagement	Mechanical				
Optimum turning radius 4WD (m)	3.6	3.6	4.1	4.1	4.1
POWER TAKE OFF					
Type	Mechanical				
Speeds (rpm)	540 / 540E or 540 / 1000 **				
PTO speed / engine speed (rpm)	540 at 2200 / 540E at 1715 or 540 at 2200 / 1000 at 2380				
PTO shaft	Exchangeable 6/21 spline, 1 3/8"				
Ground speed PTO ratio turns per wheel revolution	540 selected 8.2 / 8.9, 540E selected 10.5 / 11.4, 1000 selected 14.1 / 15.2				
HYDRAULIC SYSTEM					
Max. pump flow main hydraulic (l/min)	Standard: 40l/min Optional: 52l/min **				
Max. flow incl. steering pump (l/min)	Standard: 66.5l/min Optional: 78.5l/min **				
Control	MHC (mechanical hitch control)				
Max. lift capacity (kg)	3000	3000	3565	3565	3565
Max. number of remote valves	4	4	4	4	4
WEIGHTS*					
Minimum weight cab 2WD / 4WD (kg)	2840 / 3080	2840 / 3080	3170 / 3600	3170 / 3600	3400 / 3780
Minimum weight ROPS 2WD / 4WD (kg)	2650 / 2920	2650 / 2920	2940 / 3420	2490 / 3420	3120 / 3560
DIMENSIONS ²					
Overall length 2WD / 4WD (mm)	3918 / 3862	3918 / 3862	4032 / 3976	4115 / 4059	4115 / 4059
Minimum overall width (across rear fenders) (mm)	1808	1808	1808	1808	1808
Total height ROPS / Cab (mm)	2530 / 2512	2530 / 2512	2558 / 2540	2584 / 2566	2636 / 2618
Wheel base 2WD / 4WD (mm)	2175 / 2119	2175 / 2119	2305 / 2249	2388 / 2332	2388 / 2332
STANDARD TYRES*					
Front 2WD / 4WD	7.50-16 / 9.5-24	7.50-16 / 9.5-24	7.50-16 / 11.2-24	7.50-18 / 12.4-24	7.50-18 / 12.4-24
Rear	14.9-30	14.9-30	16.9-30	18.4-30	18.4-34

* to comply with legislation and specification in your country ** Available at extra cost 1) ECE R120 correspond to ISO TR14396 2) With Standard tyres