

Stara
Constant Evolution

SPREADERS AND AGRICULTURAL CARTS



SPREADERS AND AGRICULTURAL CARTS

SPREADERS

Specifications		Tornado 1300	Tornado 1500	Hercules 10000
Load Capacity		1300 litres/1340 Kg	1500 litres/1500 Kg	5000 litres/10000 Kg (standard wheel) 2500 litres/5000 Kg (optional wheel)
Working width		18 - 36 m	18 - 36 m	36 m (granulated products) 14 m (powdered products)
Coupling		Hydraulic system on three tractor points	Hydraulic system on three tractor points	
Rotation (TDP)		540 rpm	540 rpm	
Measurements	Length	1.3 m	1.44 m	6500 mm (with fixed heading) 6770 mm (with dirigible heading)
	Width	2.3 m	2.23 m	1910 mm
	Height	1.2 m	1.34 m (without canvas bow) 1.68 m (with canvas bow)	2500 mm (with canvas arch)
Weight		260 Kg	360 Kg	1800 Kg
Spreading system		Double disc in stainless steel	Double disc in stainless steel	18-24, 24-26 and limestone discs
Recommended tractor		Hydraulic lift system with capacity of 2.5 ton	Hydraulic lift system with capacity of 2.5 ton	Minimum power of 100 hp
Driving	Rim			7.00"x8.5" - 5 hole
	Tyre			18"x8.5" - ATV MAX
Optional	Heading			Fixed heading
	Wheel			Tyre 18.4"x30"
	Transmission		PTO drive	

AGRICULTURAL CART

Specifications	Reboke 14000 Plus
Load capacity	13 m ³ /14 tons
Grains discharge capacity	3500 litres/min
Fertilizer discharge capacity	1500 Kg/min
Discharge driving	Hydraulic engine with remote
Discharge height	4 m
Back wheel	18.4x30
Frontal wheel	18.4x26