

Stara



Twister 1500

The first Brazilian Hydraulic Distributor with variable rate

Visit our site

www.stara.com.br





- Hydraulic distributor of double disk Twister 1500 has as useful working width until 36m;
- Twister 1500 has polyethylene tank and other items that get in contact with chemical product in stainless making it stronger to corrosion;
- The removing of the polyethylene tank is easy and simple, making easy the maintenance and cleaning providing high durability to the equipment;
- The distribution disks can be driven mechanically or hydraulic;
- It reduces the rate of crushing due its width be compatible with the sprayers bars;
- Low maintenance cost.



- Polyethylene protection screen, highly strong to corrosion, avoids the entry of strange bodies guaranteeing uniformity;
- Helical mixer with rotation of just 196rpm avoids that the applied product have damages with the grinding (keeping the product granulometry) which guarantees high distance of its throwing and a uniform and accurate application.



- Flow adjusted through scales making easy so the equipment adjust to the distribution;
- All the application adjustments are made handle do not being necessary to use tools;
- Floodgates individual opening makes easy the finishing.

Twister 1500 APS



- Twister 1500 has as optional the APS System (Falcom Controller 3500 + DGPS), which makes the application with variable rate, guaranteeing an accurate and uniform application with a better profit of the products that will be applied;
- The Twister Falcon Controller 3500 can be used in all Stara's Agriculture Machines equipped with precision agriculture system, providing high versatility and less costs to the farmer, because the same controller can be used to the planting and distribution.

Technical Specifications

Load capacity	1.500 lts / 1.500 Kg
Distribution width	18 a 36 mts
Coupling	Hydraulic system on the three tractor points
Rotation (TDP)	540 rpm
Measurements	Length: 1,44 m
	Width: 2,23 m
Height	Without canvas low 1,34 m
	With canvas low 1,68 m
Weight	360 kg
Distribution system	Double disk in stainless steel
Predominant Color	Green
Distribution disks	18-24 and 24-36
Working speed	From 4 to 20 km/h
Leak	Until 400 kg/min
Recommended Tractor	Hydraulic lift system with capacity to 2,5 ton

www.stara.com.br



Talk to us
0+55 543332.2800

Stara



Stara S.A. Indústria de Implementos Agrícolas
Av. Stara, 519 - P. O. Box 53 - Não-Me-Toque/RS - Brazil
Phone/Fax: 0+55 54 3332-2800 - Zip Code 99470-000
e-mail: stara@stara.com.br