

BIG PACK BALERS



SPECIFICATIONS**LB434S****LB434R****Bale Size**

Width	47 in. (1 200 mm)	47 in. (1 200 mm)
Height	35 in. (900 mm)	35 in. (900 mm)
Length	3.9 – 9 ft. (1.2 – 2.75 m)	3.9 – 9 ft. (1.2 – 2.75 m)

Gearbox

Plunger Speed (Strokes per Minute)	48	48
Length of Stroke	27.9 in. (710 mm)	27.9 in. (710 mm)

Pick-Up

RPM – Std. / Rotor Cutter	144 / 125	144 / 125
Number of Tine Bars	4	4
Total Number of Tines	128	136
Tine Spacing	2.6 in. (66 mm)	2.6 in. (66 mm)
Width at Deflectors	88 in. (2.2 m)	92.6 in. (2 352 mm)
Width Across Tines	86.6 in. (2 200 mm)	86.6 in. (2 200 mm)

Flywheel

Diameter	37.4 in. (950 mm)	37.4 in. (950 mm)
Weight	584 lbs. (265 kg)	584 lbs. (265 kg)

Plunger

Strokes per Minute	48	48
--------------------	----	----

Knotters

Knotted Type	Heavy duty double knot	Heavy duty double knot
Number of Knotters	6	6
Twine Ball Storage Capacity	32 (16 per side)	32 (16 per side)

Dimensions - baler

Width	9.6 ft. (2.9 m)	9.6 ft. (2.9 m)
Length with Bale Shoot Folded	24.9 ft. (7 604 mm)	24.9 ft. (7 604 mm)
Length with Bale Shoot Extended	29.2 ft. (8 880 mm)	29.2 ft. (8 880 mm)
Width with Single Axle	9.8 ft. (2 984 mm)	9.8 ft. (2 984 mm)
Width with Flotation Tires	9.7 ft. (2 946 mm)	9.7 ft. (2 946 mm)
Height (at Top of Handrail)	10.25 ft. (3 133 mm)	10.6 ft. (3 223 mm)

Tires

Single – Standard	710 / 40R22.5 156D	710 / 40R22.5 156D
Tandem Axle – Optional	—	550 / 45R22.5, 620 / 50-R22.5
Tandem Axle	500 / 50 x 17 R17	500 / 50 x 17 R17

Features

Central Greasing	Auto lube	Auto lube
Knotted Greasing	Auto lube	Auto lube
Display	Pro 300 or Pro 700	Pro 300 or Pro 700
Camera	Optional	Optional
Worklights	Standard	Standard
LED	Optional	Optional

Tractor requirements

Minimum HP	125 HP (93 kW)	150 HP (110 kW)
Recommended	145 HP (108 kW)	175 HP (131 kW)
Number of Remotes	2 - Pickup / Bale Eject	3 - Pickup / Bale Eject / Knives

NOTE: Specifications may vary, confirm with your dealer.