

TRUE TANDEM 330 TURBO



SPECIFICATIONS

TRUE TANDEM 330 TURBO

Tractor Requirements

PTO Horsepower	5 to 10 HP per ft. [11 - 23 kW/m]
Remote Hydraulic Valves	Three hydraulic remote valves
Tractor Hydraulic Pressure	2200 p.s.i. [1.55 kgf/mm ²] minimum
Tractor Electrical System	12 volt with 7-pin connector
Operating Depth	1 to 2-1/2 in. [25 to 64 mm]

Frame

Mainframe	6 x 6 in. [152 x 152 mm] fore-aft tubes
25 ft.	4 x 6 in. .6 x 6 in. [102 x 152 mm. 152 x 152 mm] fore-aft tubes
34 ft.	
Gang Frame	3 x 5 in. [76 x 127 mm] Rectangular Tube
Gang Angle	18 Degrees Front and Rear

Wheels and Tires

Machine Size	25 ft.	34 ft.
Mainframe	8 Bolt, 12.5 x 15 FI	8 Bolt, 12.5 x 15 FI
Wing Frame	6 Bolt, 11L x 15 8 ply	8 Bolt, 12.5 x 15 FI
Pivoting Wing Stabilizer	6-Bolt, 7.60 x 15 8 ply	6-Bolt, 7.60 x 15

Arbor Bolt

Size	1-1/2 in. [38 mm], Round Spring Steel
Torque	800 lb-ft. [1 085 Nm]

Turbo Blade Size - Cushion Gang

	7-1/2 in. [191 mm] Spacing
Standard Blade	20 x 0.256 in. [508 x 6.5 mm]
Taper Blade [See Note 1]	18 x 0.256 in. [457 x 6.5 mm]
End Blade [See Note 2]	16 x 0.256 in. [406 x 6.5 mm]

NOTE 1: One [1] Turbo blade used per gang on outer end of front and rear gangs.

NOTE 2: One [1] Turbo blade used per gang on outer end of rear gangs only.

Basket

Basket Diameter	14 in. [356 mm]
Number of Flat Bars	10
Spring Assembly Trip Height	19.5 in. [495 mm]
Down Pressure	Adjustable 60 - 80 lb-ft. [81 - 108 Nm]

7-1/2 in. (191 mm) Turbo Blade Spacing/Tillage Width

Machine Size	25 ft.	34 ft.
Number of Blades	82	114
Number of Bearings	18	28
Tillage Width	24 ft. 7 in. (7.5 m)	34 ft. 1 in. (10.4 m)

Transport Size

Machine Size	25 ft.	34 ft.
Transport Width	15 ft. 1 in. [4.6 m]	17 ft. 10 in. [5.4 m]
Transport Height	11 ft. 2 in. [3.4 m]	13 ft. 9 in. [4.2 m]
Weight	14,990 lb [6,799 Kg]	19,900 lb [9,026 Kg]

NOTE: Specifications may vary, confirm with your dealer.