

FARMALL JX



SPECIFICATIONS**FARMALL
JX 90
CAB****FARMALL
JX 100
CAB & ROPS****FARMALL
JX 110
CAB & ROPS****ENGINE**

No. of cylinders / capacity [cm ³] / type	4 / 3,900	4 / 3,900	4 / 3,900
Rated engine power ECE R120 ¹⁾ @ engine rpm [kW/hp(CV)@rpm]	67 / 93 @ 2,300	78 / 106 @ 2,300	83 / 113 @ 2,300
Max torque ECE R120 ¹⁾ @ engine rpm [Nm@rpm]	356 @ 1400	425 @ 1400	450 @ 1400
Torque rise acc. OECD [%]	30	30.7	28.9
Fuel tank capacity [litres]	110	110	110

TRANSMISSION*

Standard	12 Fwd / 12 Rev with mechanical shuttle with hydraulic Powershuttle
----------	---------------------------------------------------------------------

DRIVE AND STEERING

Front axle standard / optional	4WD / 4WD with limited slip differential
--------------------------------	------------------------------------------

POWER TAKE OFF

Type	Servo PTO (std)
Rear pto speeds standard [rpm]	540 or 540 / 540E / proportional ground speed (depending on version)
Rear pto speeds optional [rpm]	540

HYDRAULIC SYSTEM

Max pump flow – steering / rear hitch and external services	29 / 50	29 / 50	29 / 50
Rear remote valves	2 mechanical standard / 3rd valve as option		
Rear linkage control type	MHC (Mechanical Hitch Control)		
Rear lift capacity [kg]	3,565	3,565	3,565

WEIGHTS* AND DIMENSIONS²⁾

Minimum weight [kg]	3,900	3,900	3,900
Max Permissible total weight [kg]	6,500	6,500	6,500
Max length [mm]	4322	4322	4322
Min- max track width [mm]	1628 - 2028	1628 - 2028	1628 - 2028
Max height over cab [mm]	2635	2635	2635
Wheelbase - 4WD [mm]	2422	2422	2422

STANDARD TYRES*

Front 4WD	14.9R24	14.9R24	14.9R24
Rear	18.4R34	18.4R34	18.4R34

*) to comply with legislation and specification in your country

1) ECE R120 correspond to ISO TR14396

2) with standard tyres

NOTE: Specifications may vary, confirm with your dealer.