

# FARMALL JXM



**SPECIFICATIONS****JXM 80  
2WD****JXM 80  
4WD****JXM 90  
2WD****JXM 90  
4WD****ENGINE**

Manufacturer/Model/Emission	IVECO/S8000/Tier III	IVECO/S8000/Tier III	IVECO/S8000/Tier III	IVECO/S8000/Tier III
Number of cylinders/aspiration	All models - 4/Turbocharged aftercooler			
Displacement (cm <sup>3</sup> )	3908	3908	3908	3908
Power (Hp/kW)	59.7/80	59.7/80	65.7/88	65.7/88
Rated Engine speed (rpm)	2300	2300	2300	2300
Max torque (Nm)	310 Nm @ 1400 rpm	310 Nm @ 1400 rpm	340 Nm @ 1400 rpm	340 Nm @ 1400 rpm
Injection pump type/make	Rotary/Bosch	Rotary/Bosch	Rotary/Bosch	Rotary/Bosch
Air filter	All models - Dry with pre cleaner			
Fuel filter	All models - Dual spin pn with water separator			
Fuel tank capacity (ℓ)	90	90	90	90

**PTO**

All models - Indpt. 540/1000 rpm with ground speed

**HYDRAULICS & REAR LINKAGE**

Main pump flow (ℓ/min)	54	54	54	54
Number of remote valves	All models - 2 Covertable single/double acting			
Rear linkage category, type	All models - I/II, Flex link ends, telescopic stabilisers			
Draft control	All models - Mechanical/position, draft, mixed and float controls			
Maximum lift capacity (kg)	2500 at ball ends	2500 at ball ends	2500 at ball ends	2500 at ball ends

**AXLES**

2WD front axle/ HD straight rear axle	4WD front axle HD straight rear axle	2WD front axle/ HD straight rear axle	4WD front axle HD straight rear axle
--	---	--	---

**HATCHES & DRAWBARS**

All models - Swinging drawbar with tow hook

**MISCELLANEOUS**

All models - Tool box and set of tools, English OP manual

**DIMENSIONS & WEIGHT**

Overall length including front weights (mm)	4059	4059	4059	4059
Width (mm)	2041	2041	2041	2041
Top of ROPS (mm)	2589	2589	2589	2589
Wheel base (mm)	2283	2258	2283	2258
Weight without ballast (kg)	2825	3085	2825	3085

**GROUP 104 - MECHANICAL SHUTTLE**

Transmission	All models - 12 x 12 Synchro with mechanical shuttle
Ballasting	All models - Front 70 + 6 x 40 kg All models - Rear 4 x 55kg

**GROUP 204 0 HYDRAULIC SHUTTLE**

Transmission	All models - 12 x 12 Synchro with hydraulic power shuttle
Ballasting	All models - Front 70 + 6 x 40 kg All models - Rear 6 x 55kg

**WHEELS**

Front	7.50-16 8PR	12.4-24 6PR	7.50-16 8PR	12.4-24 6PR
Rear	18.4-30 10PR	18.4-30 10PR	18.4-30 10PR	18.4-30 10PR

*NOTE: Specifications may vary, confirm with your dealer.*