

JX HIGH CLEARANCE



SPECIFICATIONS

JX95HC CAB

ENGINE	No. Of Cylinders Displacement (cm ³) kW Rated Engine Speed Max Torque (Nm) @ rpm Injection Pump Air Filter Emission Level	4 Cyl LTC 3908 71 2500 rpm 337 Nm @ 1500 rpm Distributor Type Bosch Dry Type With Dual Elements Tier 2
TRANSMISSION	Transmission Clutch Standard Gearbox Features Rear Diff. Lock	Mechanical 20 X 12 Creeper W/Mech. Shuttle All Speeds Syncromesh Mechanical
BRAKES	Service Brakes Parking Brake Control	Mechanical Operated Wet Disc Brake, Self Adjusting Not Independent Hand Lever
STEERING	Hydrostatic Steering Steering Wheel Type	Indep. Hydr. Pump, 26.5 l/Min Adjustable Tilt
PTO	Pto Clutch Pto Speeds @ 88% Of Engine Rated Speed Pto OECD/Neb. Max Power @ Rated Engine rpm Pto Shaft Type	Mechanical, Fully Independent 540 / 1000 rpm 81 Cv / 59,6 kw 1 3/8 " - 6 Spline Shaft
HYDRAULICS	Type Flow Output (l/min) / Max Pressure (Bar) Remotes	Open Centre 51.7 l/min, 190 Bar 2
HYDRAULIC POWER LIFT & 3 POINT LINKAGE	Control System Control Features (Position, Draft Etc) Draft Control 3 Point Linkage Category Max Load Capability At Ball End W/Horizon.Links	Mechanical Position / Draft / Mix Deflection Bar 2 3500 kg
4WD FRONT AXLE	Position Axle Pivoting Point Adjustable Tread Dimension (mm) Front WD Engagement	Coaxial From 1540 mm To 2267 mm Mechanical
REAR AXLE	Axle Description Adjustable Tread Dimension (mm)	Flange Type From 1503 mm to 2020 mm
OPERATOR COMPARTMENT	Drivers Compartment Type Noise Level	Platform with Rops or Suspended Platform with cab Cab - 86 db with noise reduction kit
DIMENSION & WEIGHT	Wheelbase 4WD Shipping Weight 4WD Rops (kg) Ground Clearance Front Ground Clearance Rear	2112 mm 3600 kg 619 mm 749 mm
TYRES	Front 4 Wd Rear 4 Wd	13.6 R 38 13.6 R 38

NOTE: Specifications may vary, confirm with your dealer.