

# JXT COMPACT



**SPECIFICATIONS****JXT 45  
2WD ROPS****JXT 45  
4WD ROPS**

<b>ENGINE</b>		
Number of cylinders	Simpsons/Tier III 3 Cylinder Natural Aspiration	Simpsons/Tier III 3 Cylinder Natural Aspiration
Displacement (cm <sup>3</sup> )	2700	2700
Power (Hp/kW)	31.36/42.41	31.36/42.41
Rated Engine speed (rpm)	2250	2250
Max torque (Nm)	180 Nm @ 1300 rpm	180 Nm @ 1300 rpm
Injection pump type/make	Distributor/Bosch	Distributor/Bosch
Fuel tank capacity (ℓ)	63	63
Parking brake	Independent parking brake	Independent parking brake
Battery	88 Ah	88 Ah
Exhaust system	Updraft exhaust with silencer	Updraft exhaust with silencer
<b>PTO</b>	540 PTO with double clutch	540 PTO with double clutch
<b>HYDRAULICS &amp; REAR LINKAGE</b>		
Hydraulic accessories	Additional hydraulic filter	Additional hydraulic filter
Main pump flow (ℓ/min)	29	29
Number of remote valves	1	1
Rear linkage category, type	3-point linkage with check chain, Lift-O-Matic and external service valeve	3-point linkage with check chain, Lift-O-Matic and external service valeve
Maximum lift capacity (kg)	1500 at ball ends	1500 at ball ends
<b>AXLES</b>	2WD Power steering front axle/ slow speed rear axle with differential lock	4WD Fixed front axle and propellar shaft withsealing/ slow speed rear axle with differential lock
<b>HATCHES &amp; DRAWBARS</b>	Swinging drawbar with PTO shield	Swinging drawbar with PTO shield
<b>OPERATOR AREA</b>		
Fender rails	Standard	Standard
Mirror	One side	One side
<b>MISCELLANEOUS</b>	Tool box and set of tools, OP manual	Tool box and set of tools, OP manual
<b>BALLASTING</b>		
Front (kg)	50 cast	57 cast
Rear (kg)	40 each side, total 80	40 each side, total 80
<b>DIMENSIONS &amp; WEIGHT</b>		
Overall length including front weights (mm)	3400	3400
Width (mm)	1705	1705
Top of exhaust (mm)	2270	2350
Wheel base (mm)	1965	1990
Weight without ballast (kg)	2015	2305
<b>GROUP 100</b>	8 x 2 Double clutch	
<b>GROUP 200</b>	8 x 8 Double clutch	
<b>WHEELS</b>		
Front	6.0-16	
Rear	14.9-28	

**NOTE:** Specifications may vary, confirm with your dealer.