

JXT SERIES



SPECIFICATIONS

JXT55 2WD

JXT75 2/4WD

ENGINE		
Number of cylinders	IVECO Series 8000 3 CYL NA	IVECO Series 8000 4 CYL NA
Displacement (cm ³)	2931	3908
(*) Power (Hp/kW) @ 2500 rpm	55 Hp/40 kW	75 Hp/55 kW
(*) Max torque (Nm) @ rpm / TBU %	173 Nm @ 1500 rpm / 26.7%	243 @ 1500 rpm / 18.5%
TRANSMISSION		
Transmission clutch	Mechanical	Mechanical
Total no. of speeds	8 forward, 2 reverse	8 forward, 2 reverse
Gearbox features	Constant mesh	Constant mesh
PTO		
PTO features	Fully independent	Fully independent
PTO speeds	540 rpm	540 rpm
HYDRAULICS		
Centre system (close/open)	Open	Open
Max flow output (l/min) / Max pressure (Bar)	34.0 (l/min), 190 Bar	34.0 (l/min), 190 Bar
HYD. POWER LIFT & 3 POINT LINKAGE		
Control system	Mechanical	Mechanical
Control features (Position, Draft etc)	Position / Draft / Mix	Position / Draft / Mix
Draft Control	Top link	Top link
Max load capability at ball end W/horizon.links	std. 1535 kg / opt. 2155 kg	std. 1525 kg / opt. 2155 kg
2WD FRONT AXLE		
Axle Type	Inverted U section	Inverted U section
Adjustable tread dimension (mm)	From 1400 mm to 1900 mm	From 1440 mm to 1900 mm
Minimum turning radius without braking	3.5m	3.6m
4WD FRONT AXLE		
Position axle pivoting point	Coaxial	Coaxial
Adjustable tread dimension (mm)	From 1445 mm to 1875 mm	From 1445 mm to 1875 mm
Min. turning radius W/O braking & W/4WD disengaged	4.10 m	4.26 m
REAR AXLE		
Axle description	Flange type	Flange type
Adjustable tread dimension (mm)	From 1430 mm to 2000 mm	From 1430 mm to 2000 mm
DIMENSION & WEIGHT		
Wheelbase 2WD (mm)	2050 mm	2200 mm
Wheelbase 4WD (mm)		2160 mm
Shipping weight 2WD ROPS (kg)	2155 kg	2482 kg
Shipping weight 4WD ROPS (kg)		2900 kg
Ground clearance 2WD (mm)	Front Wheel loaded radius - 200 mm	Front Wheel loaded radius - 200 mm
Ground clearance 4WD (mm)		Front Wheel loaded radius - 135 mm
Ground clearance rear (mm)	Rear Wheel loaded radius - 129 mm	Rear Wheel loaded radius - 129 mm
Height, centre rear axle to top ROPS	1650 mm	1650 mm
Tyre Size	2WD - Front 2WD - Back 4WD - Front 4WD - Back	7.50-16 16.9-30 11.2-24 16.9-30

NOTE: Specifications may vary, confirm with your dealer.